COOLING




High Efficiency Tube

Increase the number of inner groove teeth from 45 to 54, which enlarges the heat transfer area and increases heat transfer efficiency up by 7.3%.





High Efficiency Tube



CONVENIENCE



2-Ways Piping Connection

Both left and right sides of the indoor unit are possible for outstretch of connective piping and drainage hose.



Refrigerant Leakage Detection

The system will stop operation automatically to ensure safety once the refrigerant leakage is detected.



FEATURES

























SPECIFICATIONS

Model	Indoor		MOML-INCHWO	mamr-launno	MOML-18CHNO	MSMF-25CHN6	
	Outdoor		MSMF-10CRN8	MSMF-13CRN8	MSMF-19CRN8	MSMF-25CRN8	
Cooling Capacity	Rated (Min~Max)	Btu/h	9300	12150	18500	24500	
Power consumption	Rated	W	790	1092	1732	2112	
Running current	Rated	A	3.44	4.75	7.53	9.18	
CSPF(Cooling seasonal performance factor)		Wh/Wh	3.64	3.45	3.26	3.64	
Energy Efficiency Star Rating			Interior Control of Co	Management States	THE STATE OF THE S	THE STATE OF THE S	
Power supply V,Hz,Ph		220-240V~,50Hz,1Ph (Power supply to Indoor)					
Indoor unit	Indoor air flow (H)	m3/h(cfm)	593 (349)	639 (376)	790 (465)	1070 (629)	
	Indoor Sound level (H/L)	dB(A)	41/33.5/28.5	42.5/34/30	41.5/36.5/32	46/44/41	
	Dimension(W*D*H)	mm	805x194x285	805x194x285	957x213x302	1040x220x327	
	Packing (W*D*H)	mm	870x270x365	870x270x365	1035x295x385	1120x405x315	
	Net/Gross weight	Kg	8.2/10.5	8.3/10.6	11.0/14.0	13.5/16.9	

	Dillionaton(w D II)	1111111	00001040200	00001040200	SULVELOYOUS	1040XZZ0X0Z1	
	Packing (W*D*H)	mm	870x270x365	870x270x365	1035x295x385	1120x405x315	
	Net/Gross weight	Kg	8.2/10.5	8.3/10.6	11.0/14.0	13.5/16.9	
Outdoor unit	Outdoor Sound level	dB(A)	51	52	56	58	
	Dimension(W*D*H)	mm	720x270x495	765x303x555	765x303x555	946x410x810	
	Packing (W*D*H)	mm	835x300x540	887x337x610	887x337x610	1090x500x885	
	Net/Gross weight	Kg	23.1/24.9	27.3/29.7	33.6/36	60.2/66.2	
	Refrigerant Charge	g	R32/420g	R32/430g	R32/750g	R32/1500g	
	Design pressure	MPa	4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7	
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Φ6.35/Φ9.52(1/4"/3/8")	Φ6.35/Φ9.52(1/4"/3/8")	Φ6.35/Φ12.7(1/4*/1/2*)	Φ9.52/Φ15.9(3/8*/5/8",	
	Max. refrigerant pipe length	m	20	20	25	25	
	Max. difference in level	m	8	8	10	10	
Indoor-Outdoor connection wiring (Not included)		3x1.5 mm ²	3x1.5 mm ²	3x2.5 mm ²	4x2.5 mm ²		
Power supply wiring/Plug type			3x1.5 mm ² / No-plug	3x1.5 mm ² / No-plug	3x2.5 mm ² / No-plug	3x2.5 mm ² / No-plug	
Thermostat tune			Wireless Remote Control (Wire control/Wi-Fi control ontional)				

Dealer's Stamp:

- 1. The above design and specifications are subject to change of product improvement without prior notice.
- The noise level data reflects the level in anechoic chamber.
 All units are being tested and comply to ISO 5151, ISO 16358-1.

Midea Scott & English Electronics Sdn Bhd (194517-X)

No. 16, Jalan Chan Sow Lin, 55200 Kuala Lumpur Tel: 03-9221 1033 Fax: 03-9221 7204 / 03-9221 1434 / 03-9221 3509

• PENLANG No. 35, Jalan Pemiagaan Gemilang 1, Pusat Pemiagaan Gemilang, 14000 Bukit Mertajam, Pulau Pinang, Tet 04-548 3998 Fax: 04-548 9998 JOHNER No. 25, Jalan Seri Impian 1, Taman Impian Emas, 81300 Skudai, Johor. Tel: 07-562-4898 Fax: 07-557 7898 PEDAK No. 33, Persiaran Perindustrian Pengkalan 10, Kawasan Perindustrian Pengkalan, 31500 Lahat, Perak. Tel: 05-323 2529 Fax: 05-323 2529

 PANLANG No. 258, Ground Floor, Jolan Air Publin, Taman Air Publin Mewalt, 25550 Kuantan, Pahang Danul Makmur. Tel: 09-560 6668 Fax: 09-09-560 5050 MALACCA No. 385-L. Taman Perinopit Java. 75400 Perinopit. Melaka. Tet: 06-292 1940 Fax: 06-296 7107

. NOTA BIRACU PT 1436, Ground Floor, Taman Koperatif, Tanjung Chat, 15300 Kota Bharu, Kelantan. Tel/Rax: 09-143 1202. SABAN Inanom Suria Commercial Centre, Lot B, Unit 0-9, Unit 1-9, Ground Floor and First Floor, 88450, Kota Kinabalu, Sabah. Tel: 088-421 428 Fax: 088-421 421 SARAWAK 1st Floor , Lot 8517, Stutong Commercial Centre, Jalan Stutong, 95350 Kuching, Sarawak. Tel: 082-363 167 Fax: 082-366 167











PRODUCT CATALOGUE

2022




Non Inverter Wall Mounted Split (R32)

DUAL PROTECTION

Super Ionizer The Super Ionizer Generator can generate positive and negative ions. When positive ions meet negative ones, they will release enormous energy instantly and resulting in bacteria death. The redundant negative ions not only eliminates odor, dust, smoke and pollen particles in the air, but also brings more freshness. Release high-concentration positive (3.500,000 n/cm3) and negative ions (10,000,000 n/cm3) to purify the indoor air.

Dual Purification System

The Dual Filters of Midea air conditioner protect you from harmful particles to make you live a healthy life.



Automatic Self-Cleaning

The cooling coils are cleaned and dried automatically to ensure you breathe in fresh air all the time and extend the life of the air conditioner. You just need switch on the self clean function by remote control.



SMART TECHNOLOGY



So smart. it sees your needs.



Smart Kits (Optional)

Plug in Smart Kit into the air conditioner display board to enjoy the Smart Technology.



App Remote Control (APP: MSmartLife)

Control the air conditioner and set timers easily through the app. You can turn on the air conditioner before you get home and be greeted with the perfect temperature. Supports Android & IOS system.



The optimized air outlet design widens the air flow angle,

80° vertical airflow angle Conventional AC

90° horizontal airflow angle

dispersing cool air all around you for optimal comfort.

Wide-Angle Airflow

110° vertical airflow angle

120° horizontal airflow angle (Manual)

TRIPLE COMFORT

Do Not Disturb for Uninterrupted Rest

Turn on 'Do not disturb mode', AF will switch into mute mode with LED monitor light off and low wind, which provides you quiet environment.



Follow Me, Sensitive Cooling for **Your Surrounding**

'Follow Me' keeps you comfortable by measuring the air temperature around you. Keep the remote close to you, and it will measure the surrounding temperature to deliver perfectly adjusted cooling.







Remoter with 'Follow Me'


Golden Fin


The golden finned hydrophilic coil efficiently prevents bacteria from breeding and spreadig, creating a healthy and comfortable environment. It can also improve heating efficiency by accelerating defrosting. The unique anti-corrosive gold plating can withstand salty air, rain and other corrosive elements.



RELIABLE AND DURABLE







Fireproof Electronic Control Box

The electric control box uses ABS material with a 5VA flame

retardant rating, and the outer surface is covered with sheet

metal, which isolates the electric control box from fire.

an air conditioner for 10 years): the golden fin stil has good hydrophilicity (hydrophilic angle θ≤30°;

After one year of operation, the prototype with golden coating shows better performance in all working conditions than the prototype with blue coated foil.

Diamond-Cut Outdoor Unit

The air outlet in the shape of an 'Archimedes' screw and the bionic blower wheel work together to reduce the noise generated by the outdoor unit of the air conditioner. The T-shaped top cover ensures the stable operation of the internal parts and the durability of the power system.











Diamond-cut design Bionic blower wheel

Remoter without 'Follow Me